# NSN 5935-01-281-7345

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-281-7345

Body	Style:
------	--------

Hood, top opening w/clamp

## **Overall Length:**

Between 2.615 inches and 2.625 inches

# **Overall Height:**

1.850 inches

# **Overall Width:**

0.290 inches

#### **Environmental Protection:**

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

## **Mating End Quantity:**

4

# **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Polarization Method:**

Guide pin/socket

# **Shell Type:**

Hood, top opening

# **Connector Locking Method:**

Friction

## **Connector Cable Strain Relief Method:**

Cable clamp

# **Cable Opening Length:**

1.890 inches

# **Cable Opening Width:**

0.100 inches

#### **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

# **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# **Insert Material:**

Plastic diallyl phthalate glass filled single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, type ii, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 1 federal specification 2nd treatment response single mating end single contact grouping

# **Terminal Type:**

Tab, solder lug single mating end single contact grouping

# NSN 5935-01-281-7345

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



Guide Design And Location:	
D shape pin left-hand at 9 oclock v groove pin right-hand at 4: 30 oclock	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Anodize	
Shell Surface Treatment Specification:	
Mil-a-8625 military specification single treatment response	
Insert Material Specification:	
Mil-m-14, type sdg-f military specification single material response single mating end	
Included Contact Quantity:	
40 single mating end single contact grouping	
Included Contact Type:	
Square pin single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.040 gold grains, troy	
Precious Material:	
Gold	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	