Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-281-7512

# Body Style:

Straight shape

# **Overall Length:**

Between 1.526 inches and 1.556 inches

## **Overall Width:**

Between 0.479 inches and 0.509 inches

#### **Environmental Protection:**

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### **Distance Between Mounting Facility Centers:**

1.312 inches

Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

15 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

### Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

#### **Polarization Method:**

Mating end

Shell Type:

Solid

#### **Connector Locking Method:**

Friction

**Terminal Location:** 

Side single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, gr c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal

specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

**Shell Material:** 

Copper alloy

- Shell Surface Treatment:
- Cadmium and chromate

# NSN 5935-01-281-7512

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification all treatment responses **Shell Material Specification:** Qq-b-626 federal specification single material response **Insert Material Specification:** Mil-m-14, ty sdg-f military specification single material response single mating end **Included Contact Quantity:** 15 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.015 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.