

View Online at <https://aerobasegroup.com/nsn/5935-01-282-2045>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

0.447 inches

Overall Diameter:

0.312 inches

Environmental Protection:

Thermal shock resistant and moisture resistant and shock resistant and vibration resistant and salt water resistant

Cable Entrance Diameter:

Between 0.142 inches and 0.145 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Sma single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Crimp type

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

End Application:

Test set, guided missile an/dsm-130

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty ii, class i military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530, condition ht federal specification single material response single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Gold and nickel

Shell Surface Treatment Specification:

Mil-g-45204, ty ii, grade c or d, cl 1 military specification 1st treatment response and mil-c-26074 military specification 2nd treatment response

Shell Material Specification:

Qq-s-763, class 302 or 304, condition a federal specification single material response or astm-a-582, type 303, condition a assn standard single material response

Insert Material Specification:

Mil-p-19468, group a military specification single material response single mating end or l-p-403, ty vi, grade e federal specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.