# NSN 5935-01-282-2050

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-282-2050

**Body Style:** 

Straight shape, flush mount

**Overall Length:** 

1.215 inches

**Overall Height:** 

Between 2.032 inches and 2.062 inches

Overall Width:

Between 1.985 inches and 2.015 inches

**Environmental Protection:** 

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.118 inches and 0.122 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.720 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

**Distance From Mounting Shoulder To Front Face:** 

0.764 inches

**Mating End Quantity:** 

**Contact Position Arrangement Style:** 

"106, a106" single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Mating end and 3 polarization posts

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end or plastic epoxy single mating end or plastic phenolic single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

# NSN 5935-01-282-2050

Electrical Receptacle Connector - Page 2 of 2



# **Guide Design And Location:**

D shape pin left-hand at 12 oclock and d shape pin center at 12 oclock and d shape pin right-hand at 12 oclock

#### **Shell Material:**

Aluminum alloy

### **Shell Surface Treatment:**

Cadmium and chromate

### **Shell Surface Treatment Specification:**

Qq-p-416, type 2 federal specification all treatment responses

### **Shell Material Specification:**

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

### **Insert Material Specification:**

Mil-m-14, ty gdi-30f, sdg-f military specification 1st material response single mating end and mil-m-14, ty gdi-30f, sdg-f military specification 2nd material response single mating end or allied chemical 1288 bx mfr ref 3rd material response single mating end or mil-m-14 military specification 4th material response single mating end

# **Included Contact Quantity:**

106 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.106 gold grains, troy

# **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-81659 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-81659/65 government specification

# Shelf Life:

N/a

# **Unit Of Measure:**

\_

# Demilitarization:

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.