

View Online at <https://aerobasegroup.com/nsn/5935-01-282-3810>

Body Style:

Straight shape w/clamp

Overall Length:

Between 2.610 inches and 2.630 inches

Overall Height:

1.860 inches

Overall Width:

0.290 inches

Environmental Protection:

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Hood, top opening

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Cable clamp

Cable Opening Length:

1.590 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, ty ii, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 1 federal specification 2nd treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Polarization guide key code cpa

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.