

View Online at <https://aerobasegroup.com/nsn/5935-01-282-6062>

Body Style:

Straight shape, internal coupling w/backshell

Overall Length:

1.547 inches

Overall Diameter:

1.305 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

16-26 all mating ends

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

60.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

End Application:

M60a3 tts

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 type 1 cl 1 gr c military specification single treatment response single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Quantity:

26 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

For gain enhancement wire pin c t0 pin n; pot w/mil-i-46838

Precious Material And Location:

Contact surfaces gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.