

View Online at <https://aerobasegroup.com/nsn/5935-01-282-6062>

**Body Style:**

Straight shape, internal coupling w/backshell

**Overall Length:**

1.547 inches

**Overall Diameter:**

1.305 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

16-26 all mating ends

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1000.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

60.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**End Application:**

M60a3 tts

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204 type 1 cl 1 gr c military specification single treatment response single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Shell Material Specification:**

Qq-a-591 federal specification single material response

**Included Contact Quantity:**

26 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

For gain enhancement wire pin c t0 pin n; pot w/mil-i-46838

**Precious Material And Location:**

Contact surfaces gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.