Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-282-7224

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.320 inches

Overall Height:

1.125 inches

Overall Width:

1.125 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.906 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.906 inches

Distance From Mounting Shoulder To Front Face:

Between 0.708 inches and 0.728 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

"14-4, 14-04" single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

20

Thread Size:

0.875 inches

Fiig:

Electrical Receptacle Connector - Page 2 of 3



Terminal Location: Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic epoxy single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Shell Material Specification:** Qq-a-367 federal specification single material response **Included Contact Quantity:** 4 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unef **Specification Data:** 81349-mil-c-83723/72 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No



Mil-std (military Standard):

Mil-g-45204 spec.