NSN 5935-01-282-8220

Electrical Plug Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-282-8220

| Body Style: Straight shape, internal coupling Overall Length: 1.230 inches Overall Diameter: 0.782 inches Mating End Quantity: 1 Contact Position Arrangement Style: 40394 single mating end Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: |
|---|
| Overall Length: 1.230 inches Overall Diameter: 0.782 inches Mating End Quantity: 1 Contact Position Arrangement Style: 40394 single mating end Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping |
| 1.230 inches Overall Diameter: 0.782 inches Mating End Quantity: 1 Contact Position Arrangement Style: 40394 single mating end Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping |
| Overall Diameter: 0.782 inches Mating End Quantity: 1 Contact Position Arrangement Style: 40394 single mating end Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping |
| Mating End Quantity: 1 Contact Position Arrangement Style: 40394 single mating end Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping |
| Mating End Quantity: 1 Contact Position Arrangement Style: 40394 single mating end Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping |
| Contact Position Arrangement Style: 40394 single mating end Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping |
| Contact Position Arrangement Style: 40394 single mating end Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping |
| 40394 single mating end Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping |
| 10.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping |
| 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping |
| 700.0 single mating end single contact grouping |
| |
| Terminal Type: |
| |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Included Contact Quantity: |
| 4 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Test Data Document: |
| 81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-c-26482 spec. |