

View Online at <https://aerobasegroup.com/nsn/5935-01-283-2699>

Body Style:

Straight type

Overall Length:

5.380 inches

Overall Height:

0.571 inches

Overall Width:

0.298 inches

Environmental Protection:

Humidity resistant and shock resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.101 inches

Distance Between Mounting Facility Centers:

5.090 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Included Contact Quantity:

120 single mating end single contact grouping

Included Contact Type:

Flat socket single mating end single contact grouping

Precious Material:

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/25 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-55302 spec.