## NSN 5935-01-283-2954

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-283-2954

**Body Style:** 

Straight shape spring mount

**Overall Length:** 

Between 1.031 inches and 1.093 inches

**Overall Diameter:** 

1.562 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

14-dec single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

**Shell Type:** 

Solid

**Connector Locking Method:** 

Snap ring

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium and chromate

**Shell Surface Treatment Specification:** 

Qq-p-416, type ii, cl 2 federal specification all treatment responses

**Included Contact Quantity:** 

37 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round keyed

**Included Contact Type:** 

Round pin single mating end single contact grouping

## NSN 5935-01-283-2954

Electrical Receptacle Connector - Page 2 of 2



| Precious Material And Location: |
|---------------------------------|
| Contact surfaces gold           |
| Precious Material And Weight:   |
| 0.037 gold grains, troy         |
| Precious Material:              |
| Gold                            |
| Shelf Life:                     |
| N/a                             |
| Unit Of Measure:                |
|                                 |
| Demilitarization:               |
| No                              |
| Fiig:                           |
| A039b0                          |

Mil-std (military Standard):

Mil-g-45204 spec.