# NSN 5935-01-283-2961

Cadmium

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-283-2961

**Body Style:** Straight shape **Overall Length:** Between 2.620 inches and 2.650 inches **Overall Height:** 0.681 inches **Overall Width:** Between 0.590 inches and 0.620 inches **Environmental Protection:** Corrosion resistant and humidity resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 2.401 inches and 2.411 inches **Mating End Quantity: Contact Position Arrangement Style:** 9 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyester single mating end **Contact Surface Treatment Specification:** Mil-g-45204, ty ii, gr c, cl 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Metal **Shell Surface Treatment:** 

## NSN 5935-01-283-2961

Electrical Receptacle Connector - Page 2 of 2



### **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification 1st material response single mating end and mil-m-14, ty sdg-f military specification 2nd material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military specification 3rd material response single mating end **Included Contact Quantity:** 

50 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.009 gold grains, troy

**Precious Material:** 

Gold

#### **Test Data Document:**

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-24308/4 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.