

View Online at <https://aerobasegroup.com/nsn/5935-01-283-4426>

Body Style:

Straight type

Overall Length:

2.460 inches

Overall Height:

1.082 inches

Overall Width:

0.340 inches

Unthreaded Mounting Hole Diameter:

0.096 inches

Distance Between Mounting Facility Centers:

2.060 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Polarization Method:

Shell

Connector Locking Method:

Latch

End Application:

6625-01-255-1620 test set, electronic systems; ticonderoga class cg (47); forrestal class cv; los angeles class ssn (688); spruance class dd (963); arleigh burke class ddg; oliver perry class ffg; wasp class lhd; tarawa class lha; nimitz class cvn; tmde modernization equipment (temod)

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyester single mating end and glass single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty ii military specification 1st treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping

Included Contact Quantity:

34 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Weapon system essential

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.034 gold grains, troy

Precious Material:

Gold

Supplementary Features:

Mounting holes at right angle to connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.