NSN 5935-01-283-5342

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-283-5342

Body Style:

Straight shape, internal coupling

Overall Length:

1.656 inches

Overall Diameter:

0.460 inches

Environmental Protection:

Shock resistant and vibration resistant and thermal shock resistant and corrosion resistant and moisture resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Shrinkable tubing

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic fluorocarbon single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, gr c military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Shell Material Specification:

Qq-b-626 federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end or l-p-403 federal specification single material response single mating end

NSN 5935-01-283-5342

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.