Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-283-9100

View Online at https://aerobasegroup.com/nsn/5935-01-283-9100
Thread Class:
2a
Thread Direction:
Right-hand
Overall Length:
0.583 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.481 inches
Overall Height:
0.852 inches
Overall Width:
0.250 inches
Environmental Protection:
Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant
Unthreaded Mounting Hole Diameter:
0.102 inches
Flange Length:
0.625 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Sma single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Frequency Rating:
4000.0 megahertz single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
L-DIA SIDALA MATINA ANA SIDALA CONTACT ALOUNDA
Gold single mating end single contact grouping
Insert Material: Plastic single mating end

AeroBase Group

### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Tab, solder lug single mating end single contact grouping

# Shell Material:

Stainless steel

# Shell Surface Treatment:

Passivate

**Shell Material Specification:** 

Astm a582 assn standard single material response

### **Insert Material Specification:**

Mil-p-16468 military specification single material response single mating end or l-p-403, type 1 federal specification single material response single mating end

**Included Contact Quantity:** 

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.005 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Uns

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.