Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-283-9105

Body Style:
Straight shape threaded
Overall Length:
0.748 inches
Overall Diameter:
0.760 inches
Environmental Protection:
Vibration resistant and corrosion resistant and thermal shock resistant
Distance From Mounting Shoulder To Front Face:
Between 0.437 inches and 0.467 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
19-oct single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1500.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Nickel alloy single mating end single contact grouping
Contact Surface Treatment:
Tin single mating end single contact grouping and chromate single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Tin and cadmium



**Included Contact Quantity:** 

19 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

## **Special Features:**

Solder flange mounted

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0