# NSN 5935-01-283-9592

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-283-9592 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.625 inches **Overall Height:** Between 1.798 inches and 1.838 inches **Overall Width:** Between 1.798 inches and 1.838 inches **Environmental Protection:** Moisture resistant and corrosion resistant and thermal shock resistant and vibration resistant and heat resistant and cold resistant **Unthreaded Mounting Hole Diameter:** Between 0.142 inches and 0.157 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.392 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.392 inches **Distance From Mounting Shoulder To Front Face:** Between 0.878 inches and 0.898 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 116.0 and 160.0 and 191.0 and 311.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thread Length: 0.450 inches

10

**Thread Size:** 

Thready Qty Per Inch (tpi):

1.625 inches

# NSN 5935-01-283-9592

Electrical Receptacle Connector - Page 2 of 3



_					
	erm	ına	 $\alpha \alpha \alpha$	+10	'n.

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Insert Material:**

Plastic fluorosilicone single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# **Criticality Code Justification:**

Feat

# **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Steel

#### **Shell Surface Treatment:**

Cadmium and chromate

# **Shell Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses

# **Included Contact Quantity:**

92 single mating end single contact grouping

# **Included Contact Type:**

Round pin single mating end single contact grouping

# **Special Features:**

20-20 wire size pin contacts in lieu of 20-22

# **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.092 gold grains, troy

#### **Precious Material:**

Gold

# **Test Data Document:**

81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Double stub

# **Specification Data:**

81349-mil-c-28840/12 government specification

# Shelf Life:

N/a

## **Unit Of Measure:**

**Demilitarization:** 

# NSN 5935-01-283-9592

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.