Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-284-1447

Tł	hread Class:
28	a
Tł	hread Direction:
Ri	ight-hand and right-hand
B	ody Style:
St	traight shape, external coupling
0	verall Length:
33	3.66 millimeters
0	verall Height:
Be	etween 45.7 millimeters and 46.3 millimeters
0	verall Width:
Be	etween 45.7 millimeters and 46.3 millimeters
U	nable To Decode:
U	nable to decode and unable to decode
U	nable To Decode:
U	nable to decode and unable to decode
C	enter To Center Distance Between Mounting Facilities Parallel To Height:
38	3.1 millimeters
Di	istance Between Centerlines Of Mounting Facilities Parallel To Body Width:
38	3.1 millimeters
Di	istance From Mounting Shoulder To Front Face:
20	0.1 millimeters
Tł	hreaded Device Type:
Ba	ack shell and coupling facility
М	ating End Quantity:
1	
C	ontact Position Arrangement Style:
25	5-29 single mating end
C	ontact Removability:
	emovable single mating end single contact grouping
	olarization Method:
	eyway or multiple keyway
	sert Position In Deg:
	0.0 and 160.0 and 190.0 and 225.0
	hell Type:
-	olid
	onnector Locking Method:
	xternally threaded shell
	hready Qty Per Inch (tpi):
10	
	hread Size:
37	7.0 millimeters and 1.625 inches

NSN 5935-01-284-1447

Electrical Receptacle Connector - Page 2 of 3



Thread Pitch In Millimeters:

1.00

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Cadmium single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Qq-p-416 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Tolerance Class:

6g external

Included Contact Quantity:

29 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.029 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m and special acme

Specification Data:

81349-dod-c-38999/20 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

NSN 5935-01-284-1447

Electrical Receptacle Connector - Page 3 of 3

Fiig: A039b0

