## NSN 5935-01-284-1450

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-284-1450

**Body Style:** Rectangular shape **Overall Length:** 0.187 inches **Overall Height:** 0.062 inches **Body Width:** 0.105 inches **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 1.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 400.0 single mating end single contact grouping **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type ii, class 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Insert Material Specification:** Mil-m-14077, class 1 military specification single material response single mating end **Included Contact Quantity:** 3 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** 

0.003 gold grains, troy

**Precious Material And Weight:** 

Contact surfaces gold

## NSN 5935-01-284-1450

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.