## NSN 5935-01-284-2870

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-284-2870

**Body Style:** Straight shape **Overall Length:** Between 2.073 inches and 2.103 inches **Overall Height:** 0.683 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Environmental Protection:** Corrosion resistant and humidity resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 1.847 inches and 1.857 inches **Mating End Quantity: Contact Position Arrangement Style:** 25 single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Metal

## **Shell Surface Treatment:**

Cadmium

## **Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

# NSN 5935-01-284-2870

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material Specification:**

Mil-m-14, ty sdg-f or ty gpt-30f military specification single material response single mating end or mil-m-24519, ty get-30f military specification single material response single respo

## **Included Contact Quantity:**

25 single mating end single contact grouping

#### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Test Data Document:**

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

96906-mil-c-24308/2 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.