Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-285-1083

## **Body Style:**

Straight edge type

## **Overall Length:**

2.350 inches

# **Overall Height:**

0.535 inches

## **Overall Width:**

0.250 inches

## **Distance Between Mounting Facility Centers:**

2.150 inches

## **Board Accommodated Length:**

1.900 inches single board

## **Board Accommodated Width:**

0.025 inches

#### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

## **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

## **Polarization Method:**

Jackscrew

### Shell Type:

Solid

## **Connector Locking Method:**

Jackscrew-socket

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

## **Terminal Type:**

Solder well single mating end single contact grouping

## **Shell Material:**

Aluminum alloy

**Included Contact Quantity:** 

40 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

Electrical Receptacle Connector - Page 2 of 2



**Precious Material:** 

Gold

## **Test Data Document:**

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0