NSN 5935-01-285-2066

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-285-2066

Angle, shape, internal coupling

Overall Length:

1.650 inches

Overall Height:

1.350 inches

Overall Diameter:

0.750 inches

Environmental Protection:

Vibration resistant and shock resistant and corrosion resistant and moisture resistant

Cable Entrance Diameter:

0.415 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

C single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

11000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy 360 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping

NSN 5935-01-285-2066

Electrical Plug Connector - Page 2 of 2



Shell Material:
Copper alloy 360
Shell Surface Treatment:
Silver
Shell Surface Treatment Specification:
Qq-s-365 federal specification single treatment response
Shell Material Specification:
Qq-b-626 federal specification single material response
Insert Material Specification:
L-p-403 federal specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold and shell surface silver
Precious Material And Weight:
0.005 gold grains, troy and 0.100 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0