NSN 5935-01-285-2067

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-285-2067 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.490 inches **Overall Height:** Between 1.338 inches and 1.348 inches **Overall Width:** Between 1.338 inches and 1.348 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** Between 1.057 inches and 1.067 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.057 inches and 1.067 inches **Distance From Mounting Shoulder To Front Face:** Between 0.052 inches and 0.072 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 14 number 16 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 26.0 and 156.0 and 208.0 and 276.0 **Shell Type:** Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 18

Thread Size:

1.062 inches

NSN 5935-01-285-2067

Electrical Receptacle Connector - Page 2 of 3



_			 	
	arm	ına	 _ocation:	
		ша	 _UCaliUII.	

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Shell Material Specification:

Qq-a-367 federal specification single material response

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.014 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-83723/72 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

. .

NSN 5935-01-285-2067

Electrical Receptacle Connector - Page 3 of 3



Mil-std (military Standard):

Mil-g-45204 spec.