Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-285-3440

Body Style:

Straight type

Overall Length:

Between 2.620 inches and 2.650 inches

Overall Height:

Between 0.624 inches and 0.724 inches

Overall Width:

Between 0.590 inches and 0.620 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Distance Between Mounting Facility Centers:

Between 2.401 inches and 2.411 inches

Mating End Quantity:

Contact Position Arrangement Style:

50 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

1

Connector Locking Method:

Friction

End Application:

Helicopter, lamps mark iii, sh-60b; aircraft, eagle f-15; nuclear power plants; helicopter, carrier based asw, sh-60f; aircraft, viking s-3b; low altitude navigation & targeting infrared system (lantirn); joint stars target radar system; surface ship torpedo defense (sstd); aircraft, hercules c-130

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty ii, gr c, cl 1 military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Shell Material: Metal Shell Surface Treatment: Cadmium and chromate **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Insert Material Specification:** Mil-m-14, ty sdg-f or ty gpt-30f military specification all material responses single mating end **Included Contact Quantity:** 50 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Weapon system essential **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.050 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-dtl-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-dtl-24308/23 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.