

View Online at <https://aerobasegroup.com/nsn/5935-01-285-4714>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.275 inches

Overall Height:

1.578 inches

Overall Width:

1.578 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.245 inches and 1.255 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.245 inches and 1.255 inches

Distance From Mounting Shoulder To Front Face:

Between 0.556 inches and 0.587 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

22-95 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

600.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Length:

0.290 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

1.312 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and nickel single mating end all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification all treatment responses single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy 6061 or aluminum alloy 380.0 or aluminum alloy a380.0

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Shell Material Specification:

Qq-a-367, t6 federal specification 1st material response or qq-a-591 federal specification 2nd material response or qq-a-591 federal specification 3rd material response

Included Contact Quantity:

6 single mating end 1st contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.056 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms3470 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.