

View Online at <https://aerobasegroup.com/nsn/5935-01-285-6643>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.880 inches

Overall Height:

Between 1.146 inches and 1.170 inches

Overall Width:

Between 3.000 inches and 3.030 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and corrosion resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.558 inches and 0.566 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.570 inches and 2.580 inches

Distance From Mounting Shoulder To Front Face:

Between 0.615 inches and 0.630 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

51 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Mating end and guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, grade a, cl 3 or 4 military specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

51 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Furnished items - spare contact

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.051 gold grains, troy

Precious Material:

Gold

Supplementary Features:

Mounting method - spring

Test Data Document:

81349-mil-c-83733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-83733/7 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

N/A

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.