## NSN 5935-01-285-9100

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-285-9100

| View Online at https://aerobasegroup.com/nsn/5935-01-285-9100               |
|---|
| Body Style:   |
| Straight shape, external coupling   |
| Overall Height:   |
| Between 1.756 inches and 1.776 inches                                       |
| Overall Width:  |
| Between 1.756 inches and 1.776 inches                                       |
| Environmental Protection:   |
| Thermal shock resistant and vibration resistant                             |
| Unthreaded Mounting Hole Diameter:  |
| Between 0.120 inches and 0.150 inches                                       |
| Center To Center Distance Between Mounting Facilities Parallel To Height:   |
| Between 1.250 inches and 1.375 inches                                       |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 1.250 inches and 1.375 inches                                       |
| Distance From Mounting Shoulder To Front Face:                              |
| Between 0.546 inches and 0.566 inches                                       |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 22-96 single mating end   |
| Polarization Method:  |
| Keyway or multiple keyway   |
| Insert Position In Deg:   |
| 0.0   |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Bayonet pin   |
| Insert Material:  |
| Rubber single mating end  |
| Shell Material:   |
| Aluminum alloy  |
| Shell Surface Treatment:  |
| Cadmium and chromate  |
| Shell Surface Treatment Specification:                                      |
| Qq-p-416, type ii, class 3 federal specification all treatment responses    |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5935-01-285-9100

Electrical Receptacle Connector Body - Page 2 of 2



Fiig:

A039b0