NSN 5935-01-286-2815

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-286-2815
Body Style:
Straight shape, external coupling strain relief
Overall Height:
1.562 inches
Overall Width:
1.562 inches
Body Length:
1.970 inches
Environmental Protection:
Moisture resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.250 inches
Distance From Mounting Shoulder To Front Face:
0.562 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
22-67 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet slot
Connector Cable Strain Relief Method:
Cable clamp
End Application:

Terminal Location:

Back single mating end single contact grouping

5811-01-165-7408 control, communication system

NSN 5935-01-286-2815

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Iron alloy 52 single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Insert Material Specification:
Mil-m-14 military specification single material response single mating end
Included Contact Quantity:
25 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.