

View Online at <https://aerobasegroup.com/nsn/5935-01-286-2823>

**Thread Class:**

2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.585 inches

**Overall Diameter:**

1.374 inches

**Distance From Mounting Shoulder To Front Face:**

1.140 inches

**Mounting Facility Thickness:**

Between 0.125 inches and 0.375 inches

**Threaded Device Type:**

Back shell and coupling facility and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

36100 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

10

**Thread Size:**

15.0 millimeters and 0.750 inches and 20.0 millimeters

**Thread Pitch In Millimeters:**

1.00 and 1.00

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Passivate

**Thread Tolerance Class:**

6g external and 6g external

**Included Contact Quantity:**

6 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.030 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Iso m and special acme and iso m

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.