

View Online at https://aerobasegroup.com/nsn/5935-01-286-3627

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand and right-hand
Body Style:
Rectangular shape
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 3.417 inches and 3.427 inches
Overall Height:
0.966 inches
Overall Width:
1.435 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.123 inches and 0.128 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.463 inches and 0.473 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
50 single mating end
Polarization Method:
Jackscrew and shell
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
32 and 32 and 40
Thread Size:
0.138 inches and 0.138 inches and 0.112 inches
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end
Criticality Code Justification:
Feat
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize



Shell Surface Treatment Specification:

Mil-a-8625, ty i or ty ii military specification single treatment response

Shell Material Specification:

Qq-a-250/8, temper 0 federal specification single material response or qq-a-250/1, temper h12 federal specification single material response

Insert Material Specification:

Mil-m-14, ty sdg-f military specification all material responses single mating end or mil-p-19833, ty gdi-30f military specification all material

responses single mating end

Shell Guide Type And Location Designator:

C pin

Unable To Decode:

Unable to decode and unable to decode

Special Features:

Item must comply with requirements of desc production standard no. L04028; for navy nuclear propulsion plant products only

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.