Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-286-5153

| Thread Direction: |
|--|
| Right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 33.16 millimeters |
| Overall Diameter: |
| 48.0 millimeters |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 24-19 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 135.0 and 170.0 and 200.0 and 244.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Thread Size: |
| 37.0 millimeters |
| Thread Pitch In Millimeters: |
| 1.00 |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Stainless steel |
| Shell Surface Treatment: |
| Passivate |
| |

NSN 5935-01-286-5153

Electrical Plug Connector - Page 2 of 2



Thread Tolerance Class:

6h internal

Included Contact Quantity:

19 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

25-19 insert configuration

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.019 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

lso m

Specification Data:

81349-dod-c-38999/26 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.