NSN 5935-01-286-5819

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-286-5819 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** Between 1.010 inches and 1.030 inches **Overall Diameter:** Between 0.302 inches and 0.322 inches **Environmental Protection:** Heat resistant and cold resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Sma single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 335.0 single mating end single contact grouping **Contact Maximum Frequency Rating:** 12400.0 megahertz single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut **Connector Cable Strain Relief Method:** Crimp type Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material: Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-286-5819

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



Insert Material:	
Plastic polytetrafluoroethylene single mating end	
Contact Surface Treatment Specification:	
Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact group	ping
Terminal Type:	
Crimp single mating end single contact grouping	
Contact Material Specification:	
Qq-c-530 federal specification single material response single mating end single contact grouping	
Shell Material:	
Stainless steel	
Shell Surface Treatment:	
Gold	
Shell Surface Treatment Specification:	
Mil-g-45204 military specification single treatment response	
Included Contact Quantity:	
1 single mating end single contact grouping	
Included Contact Type:	
Coaxial pin single mating end single contact grouping	
Precious Material And Location:	
Contact and body surfaces gold	
Precious Material And Weight:	
0.105 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Uns	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	