## NSN 5935-01-286-6612

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-286-6612

**Body Style:** 

Right angle type

**Overall Length:** 

Between 4.740 inches and 4.760 inches

**Overall Height:** 

0.380 inches

**Overall Width:** 

Between 0.719 inches and 0.746 inches

**Environmental Protection:** 

Shock resistant and vibration resistant and salt water resistant and humidity resistant

**Unthreaded Mounting Hole Diameter:** 

0.100 inches

**Distance Between Mounting Facility Centers:** 

Between 4.444 inches and 4.456 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic polyphenylene single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, gr c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Pin single mating end single contact grouping

**Contact Material Specification:** 

Qq-c-533 federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-24519 military specification single material response single mating end

**Included Contact Quantity:** 

80 single mating end single contact grouping

## NSN 5935-01-286-6612

Electrical Receptacle Connector - Page 2 of 2



No **Fiig:** 

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Demilitarization: