Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-286-7026

| Body Style:   |
|---|
| Straight shape  |
| Overall Length:   |
| 1.312 inches  |
| Overall Height:   |
| 0.750 inches  |
| Overall Width:  |
| 0.686 inches  |
| Distance Between Mounting Facility Centers:   |
| 1.125 inches  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 20 20-20 single mating end  |
| Contact Removability:   |
| Removable single mating end single contact grouping   |
| Polarization Method:  |
| Guide pin/socket  |
| Shell Type:   |
| Solid   |
| Connector Cable Strain Relief Method:   |
| Cable clamp   |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material:  |
| Plastic diallyl phthalate single mating end   |
| Terminal Type:  |
| Crimp single mating end single contact grouping   |
| Shell Material:   |
| Aluminum alloy  |
| Shell Surface Treatment:  |
| Chromate  |
| Included Contact Quantity:  |
| 20 single mating end single contact grouping  |
| Included Contact Type:  |
| Hermaphrodite single mating end single contact grouping   |
| Precious Material And Location:   |
| Contact surfaces gold   |
|   |

Electrical Receptacle Connector - Page 2 of 2

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A039b0

