Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-286-8021

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling strain relief
Overall Length:
3.031 inches
Overall Height:
2.000 inches
Overall Width:
2.000 inches
Unthreaded Mounting Hole Diameter:
0.147 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.562 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.562 inches
Cable Entrance Diameter:
0.922 inches
Distance From Mounting Shoulder To Front Face:
Between 0.781 inches and 0.843 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
28-16 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
23.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Cable clamp



Thready Qty Per Inch (tpi):

18

Thread Size:

1.750 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Chromate and cadmium

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.020 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0