

View Online at <https://aerobasegroup.com/nsn/5935-01-286-8571>

Body Style:

Straight shape

Overall Length:

1.940 inches

Overall Height:

0.900 inches

Overall Width:

0.530 inches

Environmental Protection:

Humidity resistant and corrosion resistant and shock resistant and vibration resistant and thermal shock resistant and pressure proof

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

1.690 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

4 single mating end

Contact Maximum Dc Voltage Rating In Volts:

10000.0 single mating end single contact grouping

End Application:

Lantirn tgt pod

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Beryllium single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade c military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy 356.0

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, class 4, grade a military specification single treatment response

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.