NSN 5935-01-286-9994

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-286-9994

Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
41.06 millimeters
Overall Diameter:
41.9 millimeters
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
110.0 and 250.0
Shell Type:
Solid
Connector Locking Method:
Detent
Thread Size:
37.0 millimeters
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end all contact groupings
Criticality Code Justification:
Feat
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel

NSN 5935-01-286-9994

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment Specification:
Mil-c-26074, cl 3 or 4, gr b military specification single treatment response
Thread Tolerance Class:
6g external
Included Contact Quantity:
8 single mating end 1st contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Special Features:
Emi grounding
Precious Material And Location:
Contact survaces gold
Precious Material And Weight:
0.088 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-dod-c38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Iso m
Specification Data:
81349-dod-c-38999/46 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: