NSN 5935-01-287-0008

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-287-0008 **Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Rectangular shape Center To Center Distance Between Mounting Facilities Parallel To Length: Between 3.417 inches and 3.427 inches **Overall Height:** 0.966 inches **Overall Width:** 1.435 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.123 inches and 0.128 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.463 inches and 0.473 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 50 single mating end **Polarization Method:** Jackscrew and shell Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 32 and 40 **Thread Size:** 0.138 inches and 0.138 inches and 0.112 inches **Insert Material:** Plastic diallyl phthalate single mating end and glass fiber single mating end **Criticality Code Justification:** Feat **Shell Material:** Aluminum alloy **Shell Surface Treatment:**

Anodize

NSN 5935-01-287-0008

Electrical Receptacle Connector Body - Page 2 of 2



Shell Surface Treatment Specification:

Mil-a-8625, ty i or ty ii military specification single treatment response

Shell Material Specification:

Qq-a-250/8, temper 0 federal specification single material response or qq-a-250/1, temper h12 federal specification single material response

Insert Material Specification:

Mil-m-14, ty sdg-f military specification all material responses single mating end or mil-p-19833, ty gdi-30f military specification all material responses single mating end

Shell Guide Type And Location Designator:

D pin

Unable To Decode:

Unable to decode and unable to decode

Special Features:

Item must comply with requirements of desc production standard no. L04031; for navy nuclear propulsion plant products only

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.