Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-287-2298

# Body Style:

Straight shape

# **Overall Length:**

Between 2.714 inches and 2.744 inches

# **Overall Height:**

0.660 inches

## **Overall Width:**

Between 0.479 inches and 0.509 inches

### **Environmental Protection:**

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

### Distance Between Mounting Facility Centers:

Between 2.495 inches and 2.505 inches

### Mating End Quantity:

**Contact Position Arrangement Style:** 

62 single mating end

### **Contact Removability:**

Removable single mating end single contact grouping

## **Polarization Method:**

Mating end

### Shell Type:

Solid

1

## **Connector Locking Method:**

Friction

**Terminal Location:** 

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Insert Material:**

Plastic diallyl phthalate single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type 2, gr c, cl 1 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping

# Shell Material:

Metal

# Shell Surface Treatment:

Cadmium



## **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-m-24519, ty gpt-3 of or ty get-30f military

specification single material response single mating end

## **Included Contact Quantity:**

62 single mating end single contact grouping

#### Included Contact Type:

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

#### **Precious Material And Weight:**

0.062 gold grains, troy

#### **Precious Material:**

Gold

### Test Data Document:

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-c-24308/4 government specification

Shelf Life:

N/a

# Unit Of Measure:

Demilitarization:

No

--

Fiig:

#### A039b0

Mil-std (military Standard):

Mil-g-45204 spec.