Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-287-4405

2a Thread Direction: Right-hand Body Style: Straight shape, external coupling Overall Length: 1.141 inches Overall Height: 1.188 inches Overall Width: 1.188 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width 0.906 inches Distance From Mounting Shoulder To Front Face: 0.907 inches Distance Trope: Coupling facility Mating End Quantity: 1
Right-handBody Style:Straight shape, external couplingOverall Length:1.141 inchesOverall Height:1.188 inchesOverall Width:1.188 inchesCenter To Center Distance Between Mounting Facilities Parallel To Height:0.906 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Widthet0.906 inchesDistance From Mounting Shoulder To Front Face:0.672 inchesThreaded Device Type:Coupling facilityMating End Quantity:
Body Style: Straight shape, external coupling Overall Length: 1.141 inches Overall Height: 1.188 inches Overall Width: 1.188 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches Distance From Mounting Shoulder To Front Face: 0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
Straight shape, external coupling Overall Length: 1.141 inches Overall Height: 1.188 inches Overall Width: 1.188 inches Overall Width: 1.188 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width 0.906 inches Distance From Mounting Shoulder To Front Face: 0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
Overall Length: 1.141 inches Overall Height: 1.188 inches Overall Width: 1.188 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches Distance From Mounting Shoulder To Front Face: 0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
1.141 inches Overall Height: 1.188 inches Overall Width: 1.188 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width 0.906 inches Distance From Mounting Shoulder To Front Face: 0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
Overall Height: 1.188 inches Overall Width: 1.188 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches Distance From Mounting Shoulder To Front Face: 0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
 1.188 inches Overall Width: 1.188 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches Distance From Mounting Shoulder To Front Face: 0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
Overall Width: 1.188 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches Distance From Mounting Shoulder To Front Face: 0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
1.188 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches Distance From Mounting Shoulder To Front Face: 0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches Distance From Mounting Shoulder To Front Face: 0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches Distance From Mounting Shoulder To Front Face: 0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches Distance From Mounting Shoulder To Front Face: 0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
0.906 inches Distance From Mounting Shoulder To Front Face: 0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
Distance From Mounting Shoulder To Front Face: 0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
0.672 inches Threaded Device Type: Coupling facility Mating End Quantity:
Threaded Device Type: Coupling facility Mating End Quantity:
Coupling facility Mating End Quantity:
Mating End Quantity:
1
Contact Position Arrangement Style:
"14s-6, 11-6" single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Shell Type:
Solid
Thready Qty Per Inch (tpi):
20
Thread Size:
0.875 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end



Terminal Type: Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 6 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces silver **Precious Material:** Silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0