## NSN 5935-01-287-7578

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-287-7578 **Body Style:** Straight shape, external coupling **Overall Length:** 1.938 inches **Overall Height:** 2.000 inches Overall Width: 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Mating End Quantity: Contact Position Arrangement Style:** 28-21 single mating end **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 110.0 **Terminal Type:** Solder well single mating end single contact grouping **Included Contact Quantity:** 37 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Test Data Document:** 81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5935-01-287-7578

Electrical Receptacle Connector - Page 2 of 2



Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.