NSN 5935-01-287-8474

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-287-8474

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

135.3 millimeters

Overall Diameter:

66.3 millimeters

Environmental Protection:

Shock resistant and vibration resistant and waterproof and heat resistant and cold resistant

Cable Entrance Diameter:

Between 23.4 millimeters and 35.0 millimeters

Mating End Quantity:

4

Contact Position Arrangement Style:

36-10 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and rhodium single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

NSN 5935-01-287-8474

Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification all treatment responses
Included Contact Quantity:
48 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold or contact surfaces rhodium or contact surfaces silver
Precious Material And Weight:
$0.048\ gold\ grains,\ troy\ or\ 0.048\ rhodium\ grains,\ troy\ or\ 0.048\ silver\ grains,\ troy$
Precious Material:
Gold or rhodium or silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.