## NSN 5935-01-288-4799

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-288-4799

**Body Style:** Straight shape, flush mount **Overall Length:** 0.906 inches **Overall Height:** 1.687 inches **Overall Width:** 3.375 inches **Environmental Protection:** Heat resistant and cold resistant and pressure proof **Unthreaded Mounting Hole Diameter:** 0.144 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.875 inches **Distance From Mounting Shoulder To Front Face:** 0.062 inches **Mating End Quantity: Contact Position Arrangement Style:** 32c2 single mating end **Contact Removability:** Removable single mating end single contact grouping **End Application:** Kc-135 aircraft **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping or silver single mating end single contact grouping **Contact Surface Treatment Specification:** Qq-c-36s federal specification 1st treatment response single mating end single contact grouping and mil-g-45204 military specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Contact Material Specification:** Qq-c-533 federal specification single material response single mating end single contact grouping

**Shell Material Specification:** 

**Shell Material:** Aluminum alloy

Qq-a-591/a-380 federal specification single material response

## NSN 5935-01-288-4799

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
32 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

A039b0

Fiig:

Mil-std (military Standard):

Mil-g-45204 spec.