

View Online at https://aerobasegroup.com/nsn/5935-01-289-1182

| Thread Class: |
|---|
| 2a and 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Rectangular shape |
| Overall Length: |
| Between 2.703 inches and 2.733 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| Between 2.277 inches and 2.287 inches |
| Overall Height: |
| 1.307 inches |
| Overall Width: |
| Between 0.870 inches and 0.880 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 0.463 inches and 0.473 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 50 single mating end |
| Polarization Method: |
| Jackscrew |
| Connector Locking Method: |
| Jackscrew-socket |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.138 inches |
| Insert Material: |
| Glass fiber single mating end and plastic diallyl phthalate single mating end |
| Insert Material Specification: |
| Mil-m-14, ty sdg-f military specification all material responses single mating end or mil-p-19833, ty gdi-30f military specification all material |
| responses single mating end |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.