## NSN 5935-01-289-2079

Plug-in Electronic Components Socket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-289-2079 **Body Material:** Any acceptable **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Top mount w/studs **Overall Length:** Between 1.469 inches and 1.499 inches **Overall Height:** Between 0.589 inches and 0.599 inches **Overall Width:** Between 0.391 inches and 0.421 inches **Mounting Slot Width:** Between 0.123 inches and 0.131 inches **Body Mounting Hole Accommodation Length:** 0.875 inches **Body Mounting Hole Accommodation Width:** 0.469 inches **Distance Between Mounting Facility Centers:** 1.344 inches **Mounting Hole Style:** Rectangular, w/external slots **Contact Maximum Current Rating In Amps:** 3.0 **Contact Material:** Any acceptable **Contact Surface Treatment:** Gold and silver **Accommodated Contact Quantity: Polarization Type:** Center key hole **Projection Length Below Mounting Surface:** Between 0.235 inches and 0.265 inches **Mounting Method:** Threaded stud **Mounting Type For Which Designed:** Chassis

Thready Qty Per Inch (tpi):

56

## NSN 5935-01-289-2079

Plug-in Electronic Components Socket - Page 2 of 2



Thread Size:
0.086 inches
Contact Position Arrangement Style:
Dual in line
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.008 gold grains, troy and 0.008 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A02300