

View Online at <https://aerobasegroup.com/nsn/5935-01-289-2079>

**Body Material:**

Any acceptable

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Top mount w/studs

**Overall Length:**

Between 1.469 inches and 1.499 inches

**Overall Height:**

Between 0.589 inches and 0.599 inches

**Overall Width:**

Between 0.391 inches and 0.421 inches

**Mounting Slot Width:**

Between 0.123 inches and 0.131 inches

**Body Mounting Hole Accommodation Length:**

0.875 inches

**Body Mounting Hole Accommodation Width:**

0.469 inches

**Distance Between Mounting Facility Centers:**

1.344 inches

**Mounting Hole Style:**

Rectangular, w/external slots

**Contact Maximum Current Rating In Amps:**

3.0

**Contact Material:**

Any acceptable

**Contact Surface Treatment:**

Gold and silver

**Accommodated Contact Quantity:**

8

**Polarization Type:**

Center key hole

**Projection Length Below Mounting Surface:**

Between 0.235 inches and 0.265 inches

**Mounting Method:**

Threaded stud

**Mounting Type For Which Designed:**

Chassis

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.086 inches

**Contact Position Arrangement Style:**

Dual in line

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.008 gold grains, troy and 0.008 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02300