Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-289-4876



# Thread Class:

2b

Thread Direction:

Right-hand

#### **Body Style:**

Angle shape w/cable clamp

#### **Overall Diameter:**

1.461 inches

#### Body Angle In Deg:

90.0

#### Cable Entrance Diameter:

0.455 inches

**Threaded Device Type:** 

Coupling facility

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

20-4 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

41.0 single mating end single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

940.0 single mating end single contact grouping

#### Contact Maximum Dc Voltage Rating In Volts:

1300.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### Insert Position In Deg:

45.0

Shell Type:

Solid

#### **Connector Locking Method:**

Internally threaded coupling ring

# Connector Cable Strain Relief Method:

Cable clamp

# Distance From Centerline To Connector End:

2.322 inches

# Distance From Centerline To Cable End:

2.166 inches

# Thready Qty Per Inch (tpi):

18

# NSN 5935-01-289-4876

Electrical Plug Connector - Page 2 of 2



## Thread Size:

1.250 inches

#### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Metal single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

#### **Insert Material:**

Rubber single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd

treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

**Included Contact Quantity:** 

4 single mating end single contact grouping

#### Included Contact Type:

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

#### **Precious Material And Weight:**

0.020 gold grains, troy and 0.020 silver grains, troy

#### **Precious Material:**

Gold and silver

#### Thread Series Designator:

Unef

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.