

View Online at <https://aerobasegroup.com/nsn/5935-01-289-4877>

**Overall Height:**

1.453 inches

**Overall Width:**

1.453 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.156 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.156 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

41 number 20 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

600.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

225.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Shell Material Specification:**

Qq-a-591 federal specification single material response

**Special Features:**

All contacts are wired to case

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.041 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.