

View Online at <https://aerobasegroup.com/nsn/5935-01-289-4881>

Body Style:

Straight type

Overall Length:

Between 0.710 inches and 0.730 inches

Overall Width:

Between 0.065 inches and 0.075 inches

Body Height:

Between 0.565 inches and 0.635 inches

Environmental Protection:

Moisture resistant and salt water resistant and shock resistant and vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Connector Locking Method:

Friction

End Application:

Inertial navigational system an/wsn-3av5

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, gr c, cl 1 military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Crimp single mating end single contact grouping

Insert Material Specification:

Mil-p-46174, gr e, cl 40 military specification single material response single mating end or mil-m-24519, tygpt-30f military specification single material response single mating end

Included Contact Quantity:

12 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Contacts 2 and 14 omitted for polarization; cavities filled with epoxy

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.012 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.