

View Online at https://aerobasegroup.com/nsn/5935-01-289-5235

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, rectangular
Overall Length:
Between 3.362 inches and 3.382 inches
Overall Height:
Between 0.860 inches and 0.880 inches
Overall Width:
Between 2.582 inches and 2.602 inches
Environmental Protection:
Corrosion resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.463 inches and 0.473 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 2.080 inches and 2.100 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Polarization Method:
Guide pin/socket
Connector Locking Method:
Jackscrew
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyester single mating end
Insert Material Specification:
Mil-m-14, ty sdg-f or ty gdi-30f military specification 1st material response single mating end and mil-m-14, ty sdg-f or ty gdi-30f military

specification 2nd material response single mating end or mil-m-24519 military specification 3rd material response single mating end

Test Data Document:

81349-mil-c-28731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

813/0-mil-c-28731/31 government execification



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.